



Frosted frameless mirror with clip fasteners and 1/4" plate glass with polished edges:

### Product Materials

**MIRROR:** first quality 1/4" float glass and thermosetting infrared-cured paint backing. Manufactured in accordance with ASTM C 1036 and ASTM C 1503. Edges ground and polished smooth.

### Design Option Codes

| Code | Description              |
|------|--------------------------|
| -S   | Solid acid-etched border |

### Installation

Verify all rough-in dimensions prior to installation. Secure mounting clips (metal) to wall with screws included, then engage mirror into clips.

### Guide Specification

Frameless mirror shall be of first quality 1/4" float glass, guaranteed for 15 years against silver spoilage. Edges ground and polished smooth.

**Frosted Frameless Mirror shall be Bradley Model 747F.**



### ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

### Models

| Width (Inches) | Height (Inches) | Design Option | Standard Model Number |
|----------------|-----------------|---------------|-----------------------|
| 18"            | 30"             | S             | 747F-018300S          |
| 18"            | 36"             | S             | 747F-018360S          |
| 24"            | 36"             | S             | 747F-024360S          |

### Mounting Height Guide

| Dim. "A":  | For Dim. "A" | Bottom of Unit |
|--|--------------|----------------|
| Mirror's bottom edge of the reflecting surface to finished floor | 40" (1016mm) | 37" (9406mm)   |
|  | 37" (940mm)  | 34" (864mm)    |
|  | 34" (864mm)  | 31" (787mm)    |

